

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE			2. REPORT TYPE Abstract and Viewgraphs		3. DATES COVERED	
4. TITLE AND SUBTITLE VMCA Flight Test of the Carrier-Landin', Mail-Hauling' C-2A			5a. CONTRACT NUMBER 5b. GRANT NUMBER 5c. PROGRAM ELEMENT NUMBER			
			5d. PROJECT NUMBER 5e. TASK NUMBER 5f. WORK UNIT NUMBER			
6. AUTHOR(S) Mike Wagner Chuck Webb						
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Air Warfare Center Aircraft Division 22347 Cedar Point Road, Unit #6 Patuxent River, Maryland 20670-1161			8. PERFORMING ORGANIZATION REPORT NUMBER			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Naval Air Systems Command 47123 Buse Road Unit IPT Patuxent River, Maryland 20670-1547			10. SPONSOR/MONITOR'S ACRONYM(S)			
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)			
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT The C-2A is a Navy, carrier-based aircraft used for the Carrier On-Board Delivery (COD) mission. The aircraft was recently equipped with an L-Probe pitot-static system. Comparison of L-Probe data with previous pitot-static data suggested that approach speeds might be below published Vmc. Analysis of original Vmc flight test suggested that actual Vmc had not been reached. Also, more mission representative Vmc techniques developed in recent years, could provide a more accurate Vmc number. Flight tests were conducted to reassess Vmc using the L-probes as the primary pitot-static source. Vmc tests were conducted in 10 flights, 23 hours and included over 40 actual engine shutdowns. Both the Classic (FTM-103) and Waveoff techniques were used during the flight test. The techniques were conducted at intermediate airspeed ranges for comparative purposes. Both techniques required additional analysis and clarification to ensure minimal airspeed change from the time the engine was secured to the time initial control inputs were made and subsequent. Several other techniques/test conditions were employed to ensure a more conservative Vmc number and proper mission relation. Finally, new airspeed data evaluation considerations helped provide final Vmc numbers for fleet use. The lower Vmc number will permit approach to landings over a broader weight range. The C-2A Vmc test effort not only yielded new, more accurate Vmc numbers for the C-2A aircraft, it also yielded many lessons learned that will be of assistance to future Vmc testers.						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF: a. REPORT b. ABSTRACT c. THIS PAGE			17. LIMITATION OF ABSTRACT Unclassified	18. NUMBER OF PAGES 22	19a. NAME OF RESPONSIBLE PERSON Mike Wagner / Chuck Webb 19b. TELEPHONE NUMBER (include area code) (301) 757-3881 / 757-2900	

Standard Form 298 (Rev. 8-98)

Approved by ANSI Std. Z39-18

DATA QUALITY INSPECTED 4

20000607 011

EXHIBIT ONE

[Set of PowerPoint slides to be presented at the Test Pilot School Technical Symposium on 4/14/00, titled, "V_{MCA} Flight Test of the Carrier-Landin', Mail-Haulin' C-2A"]

EXHIBIT TWO

[Use – Included in the agenda of topics to be handed out by the Test Pilot School the day of the Symposium on 4/14/00]

Abstract - V_{MCA} Flight Test Of The Carrier-Landin', Mail-Haulin' C-2A


The C-2A is a Navy, carrier-based aircraft used for the Carrier On-board Delivery (COD) mission. The aircraft was recently equipped with an L-Probe pitot-static system. Comparison of L-Probe data with previous pitot-static data suggested that approach speeds might be below published V_{mc}. Analysis of original V_{mc} flight test suggested that actual V_{mc} had not been reached. Also, more mission representative V_{mc} techniques developed in recent years, could provide a more accurate V_{mc} number. Flight tests were conducted to reassess V_{mc} using the L-probes as the primary pitot-static source. V_{mc} tests were conducted in 10 flights, 23 hours and included over 40 actual engine shutdowns. Both the Classic (FTM-103) and Waveoff techniques were used during the flight test. The techniques were conducted at intermediate airspeed ranges for comparative purposes. Both techniques required additional analysis and clarification to ensure minimal airspeed change from the time the engine was secured to the time initial control inputs were made and subsequent. Several other techniques/test conditions were employed to ensure a more conservative V_{mc} number and proper mission relation. Finally, new airspeed data evaluation considerations helped provide final V_{mc} numbers for fleet use. The lower V_{mc} number will permit approach to landings over a broader weight range. , The C-2A V_{mc} test effort not only yielded new, more accurate V_{mc} numbers for the C-2A aircraft, it also yielded many lessons learned that will be of assistance to future V_{mc} testers.

V_{MCA} Flight Test of the Carrier-Landin', Mail-Haulin' C-2A

Michael J. Wagner (5.5)

Chuck Webb (4.11)

14 Apr 2000




2

V_{MCA} - Background

- Installed and tested L-shaped pitot-static probes
- Test results showed approach speeds below some historical approach speeds and those published in Aircraft Recovery Bulletins. Also below V_{MCA} for nearly all landing weights.
- Approach Speed Chart - reveals need to verify V_{MCA}

Config PA(20) Approach Speeds



V_{MCA} - Background

- Current NATOPS V_{MCA} - 100 KIAS
 - 100 KCAS came from C-2A Increased Gross Weight testing
 - 100 KCAS transposed to 100 KIAS - date unknown
 - Accuracy - According to report data, at 100 KCAS additional rudder control power is still available

V_{MCA} - Scope of Tests

- Conditions
 - WO(20) - gear down, flaps 20
 - WO(30) - gear down, flaps 30
 - Power - defined by test technique
 - Altitude - 4000 ft
- 10 flights, 23 hours, V_{MCA} Static and Dynamic
- Techniques Used
 - Classic (method used to obtain current V_{MCA})
 - Waveoff (method used in E-2C PLUS tests, considered more mission representative, yielded ultimate results)

Classic Technique

- Stabilize in climb at target airspeed with max power (4600 ISHP/engine)
- At target altitude copilot fails desired engine by rapidly pulling Condition Lever to FX (simulated - power lever to Flight Idle)
- No inputs for 1 second (except longitudinal inputs to control airspeed loss if desired)
 - Apply recovery inputs as required

Classic Technique: ProS and Cons

- Pros
 - Repeatable
 - Stable conditions at maximum power
- Cons
 - Not mission representative
 - Airspeed control following engine failure
 - large airspeed loss
 - large longitudinal push over required in an attempt to minimize airspeed loss
 - Extremely nose high attitude

Waveoff Technique

- Establish 500 FPM ROD
- At target airspeed and altitude, rapidly advance power levers to max
- On power addition, copilot immediately fails desired engine by pulling Condition Lever to FX (simulated - power lever to Flight Idle)
- No inputs for 1 second (except small longitudinal inputs to control airspeed gain)
- Apply recovery inputs as required

Waveoff Technique: Pros and Cons

- Pros
 - Very mission representative (engine failure on waveoff)
 - Better airspeed control than Classic following engine failure
- Cons
 - Airspeed control following engine failure
 - acceleration during power addition
 - Dynamic engine response with power addition
 - Can be non-repeatable inputs on waveoff and recovery

Waveoff Technique Adjustments

Method	W aveoff	FX/PL Chop <----- 1 sec delay ----->	Recovery
Some			
Rudder			
More			
Rudder			
Open			
Loop			
Closed			
Loop			

Waveoff Technique: Built-In Conservatism

- Very rapid power addition (PGS to max power in ~0.2 seconds)
 - Mechanical Power Lever Stop - adjustable for test day conditions. Prevent engine over-torque or over-temp on rapid power addition
- Minimized airspeed acceleration
 - Adding power on one engine while failing other
 - Permitted nose to rise slightly on power addition

Waveoff Technique: Built-In Conservatism (cont'd)

- Aft CG
- 1 second delay from engine failure to initial recovery inputs
- Different test pilot used for end points

V_{MCA} Criteria:

- Angular acceleration fails to reverse immediately at control input
- The time from initiation of rudder input to 0 yaw rate is greater than 2 sec
- 23 1/2 units AOA
- Greater than 15 deg sideslip


V_{MCA} Criteria (cont'd):

- Greater than 20 deg bank angle
- Greater than 20 deg heading change
- Static single engine control airspeed
- Recovery is unsafe or required excessive workload for the average pilot


Results

- Left engine was determined to be critical from previous testing and V_{mc} Static
- Results indicate a lower V_{MCA} than previously reported
 - V_{MCA} flaps 20 - 95 KIAS
 - V_{MCA} flaps 30 - 96 KIAS
- Although controllable above V_{MCA} , positive SERC performance is not assured

Engine Response



Recovery



Waveoff Technique: Another Possible Approach

- Stabilize on target airspeed with 1/2 max power on each engine
- Concurrently -
 - FX target engine
 - Add Max power on other engine
- Recovery inputs after 1-2 second delay
 - Technique minimizes accel - no net change in thrust
 - Not tested here

Lessons Learned / Summary

- Plan dual-engine waveoff control input profiles and consider their impact on V_{MCA} control inputs
- Waveoff technique - operating engine may not be at maximum power when attaining V_{MCA} depending on engine response
- Adequate single engine performance may not be assured at V_{MCA} - ex.: rate of climb

Lessons Learned / Summary

- C-2A NATOPS changes
 - New V_{MCA}
 - ‘Engine Failure During Waveoff’ - descriptive paragraph not previously incorporated